

# ALUMINIUM XLPE SECTOR CABLE




AUSTRALIA PACIFIC ELECTRIC CABLES

0.6/1KV to AS/NZS 4026 & 5000.1

**Conductor:** Aluminium  
Compacted plain hard drawn

**Insulation:** XLPE X-90

**Sheath:** PVC 5V90 UV  
Conductor temperature 90°C



**Standard Colours:**

**Cores:** Red, White, Blue & Black

**Outer Sheath Colour:** Black

Nominal Conductor area	Nominal Conductor diameter	Average Insulation thickness	Diameter Over laid-up cores	Outer Sheath Nominal thickness	Approx. overall diameter	Approx. mass	Product Code
mm <sup>2</sup>	mm	mm	mm	mm	mm	kg/100m	
240.0	17.1 X 24.7	1.7	49.6	2.8	56.5	382.0	SCT240A04

#### Brisbane Office and Factory

89 Platinum Street,  
Crestmead, Qld 4132  
P: 07 3802 3651  
E: [brisesales@apeccables.com.au](mailto:brisesales@apeccables.com.au)

#### Melbourne Sales & Distribution

188 Holt Parade,  
Thomastown, VIC 3074  
P: 03 9465 1188  
E: [salesmdc@apeccables.com.au](mailto:salesmdc@apeccables.com.au)

#### Perth Sales & Distribution

638 Casella Place  
Kewdale, WA 6105  
P: 08 9350 1300  
E: [salespdc@apeccables.com.au](mailto:salespdc@apeccables.com.au)