

PVC POWER CABLES



AUSTRALIA PACIFIC ELECTRIC CABLES

Standard Colours

Cores: Red and Black or
Red and White


Sheath: White

*Also available in Red Sheath

*Orange sheath – 10mm & 16mm

PVC Insulated, PVC Sheathed,

Two core flat,
450 / 750 V to AS/NZS 5000.2



Conductor: annealed copper.

Insulation: PVC V90

Sheath: PVC 3V90

compounds for continuous
conductor temperature of
90°C.

Nominal Conductor area mm ²	Average Insulation thickness mm	Average Sheath thickness mm	Approx. overall dimensions mm	Approx. mass kg/100m	Product Code
1.0	0.6	0.9	6.7 x 4.3	5.4	VFM113C02RB VFM113C02RW
*1.5	0.6	0.9	7.4 x 4.7	6.7	VFM105C02RB VFM105C02RW *VFM105C02RWR
2.5	0.7	1.0	9.1 x 5.6	10.5	VFM205C02RB VFM205C02RW
4.0	0.8	1.1	10.8 x 6.5	15.5	VFM004C02RB VFM004C02RW
6.0	0.8	1.1	11.9 x 7.1	20.3	VFM006C02RB VFM006C02RW
10.0	1.0	1.2	14.8 x 8.7	32.2	VFM010C02RB *VFM010C02RBO
16.0	1.0	1.3	17.1 x 9.9	46.5	VFM016C02RB *VFM016C02RBO

Brisbane Office and Factory

89 Platinum Street,
Crestmead, Qld 4132
P: 07 3802 3651
E: brisesales@apeccables.com.au

Melbourne Sales & Distribution

188 Holt Parade,
Thomastown, VIC 3074
P: 03 9465 1188
E: salesmdc@apeccables.com.au

Perth Sales & Distribution

638 Casella Place
Kewdale, WA 6105
P: 08 9350 1300
E: salespdc@apeccables.com.au