



AUSTRALIA PACIFIC ELECTRIC CABLES

Instrumentation Cable

0.75 Overall Shield Cu/PVC/SCR/PVC

PVC Insulated, PVC Sheathed



Conductor: Plain Annealed Copper Class 2 to AS1125

Insulation: PVC V90

Sheath: PVC 5V90

Drain Wire: Stranded Tinned Copper (7/0.2mm)

Voltage: 110/150V

Standard Colours

Cores: Black & White numbered pairs

Sheath: Black

0.75mm Overall Shield (Cu/PVC/SCR/PVC)			
Pair Count	Overall Diameter mm	Approx mass kg/100m	Product Code
1	4.1	4.1	INSV00075PO1B
2	6.8	7.5	INSV00075PO2B
3	7.2	10.1	INSV00075PO3B
4	8.1	12.4	INSV00075PO4B

Brisbane Office and Factory

89 Platinum Street,
Crestmead, Qld 4132
P: 07 3802 3651
E: bnesales@apeccables.com.au

Melbourne Sales & Distribution

188 Holt Parade,
Thomastown, VIC 3074
P: 03 9465 1188
E: salesmdc@apeccables.com.au

Perth Sales & Distribution

638 Casella Place
Kewdale, WA 6105
P: 08 9350 1300
E: salespdc@apeccables.com.au