PVC POWER CABLES



AUSTRALIA PACIFIC ELECTRIC CABLES

PVC Insulated, PVC Sheathed, Single core, Double Insulated 1.0 to 16mm² 450 / 750 V to AS 5000.2



Conductor: annealed copper. Insulation: PVC V90 Sheath: PVC 3V90 compounds for continuous conductor temperature of 90°C.

Standard Colours Core: Red or Black. Sheath: White (1mm avail in White/White)

Nominal Conductor area mm²	Average Insulation mm	Approx. mm	Approx. overall mm	Approx. mass kg/100m	Product Code
1.0	0.6	0.8	4.1	2.9	VVM113
1.5	0.6	0.8	4.4	3.5	VVM 105
2.5	0.7	0.8	5.2	5.2	VVM205
4.0	0.8	0.9	6.1	7.7	VVM004
6.0	0.8	0.9	6.7	10.0	VVM006
10.0	1.0	0.9	8.1	15.6	VVM010
16.0	1.0	1.0	9.3	22.7	VVM016

6.0 to 35mm² 0.6/1kv to AS 5000.1 Insulation & sheath: PVC V90

The below items are available in our Perth Distribution Centre. Various colour options are available.

Nominal Conductor area mm ²	Average Insulation thickness mm	Average sheath thickness mm	Approx. overall diameter mm	Approx. mass kg/100m	Product Code
6.0	1.0	1.4	8.2	12.3	VVM0065K1
10.0	1.0	1.4	9.1	17.2	VVM0105K1
16.0	1.0	1.4	10.1	24.0	VVM0165K1
25.0	1.2	1.4	12.0	35.6	VVM025
35.0	1.2	1.4	13.1	46.5	VVM035

Brisbane Office and Factory

89 Platinum Street, Crestmead, Qld 4132 P: 07 3802 3651 E: <u>bnesales@apeccables.com.au</u>

Melbourne Sales & Distribution

188 Holt Parade, Thomastown, VIC 3074 P: 03 9465 1188 E: <u>salesmdc@apeccables.com.au</u>

Perth Sales & Distribution

638 Casella Place Kewdale, WA 6105 P: 08 9350 1300 E:salespdc@apeccables.com.au